

■ Mounted Equipment Of Automatic Fire Extinguisher

■ For Highly Dangerous Goods

▶ Description

This applied to the facility and place to use and dangerous materials (gold Mercury, pyrophoric) and to protect life and property were developed as a safe and complete digestion initial purpose products

▶ Features

- Unlike other extinguishing agents are safe and clean debris after digestion extinguishing does not occur
- The system can be operated by emergency power in case of power failure (About 60 minutes)
- Excellent control using a small advanced IC circuit
- The operating conditions of the fire extinguisher is stored in real time, it can be checked if necessary (There is no loss of data even in the event of a power failure)
- It is easy to use LCD DISPLAY unit installed in the control unit operating status is indicated by letters
- The real-time monitoring of operational status or RS-485 communication over the presence of fire extinguishers

CE Certified



SPECIFICATION				
Model		NIG-1GG0241	NIG-2GG0241	NIG-3GG0241
Size (mm)	W	340	500	570
	D	327	337	379
	H	1,140	1,140	1,590
Weight		50kg	65kg	153kg
Extinguishing Containers		2m³ x 1BOTTLE	2m³ x 2BOTTLE	6m³ x 2BOTTLE
Extinguishing Agents		N2		
Use Temperature		-5°C ~ 40°C		
Power		FREE VOLTAGE (AC 90V ~260V), 50/60Hz		
Emergency Power		DC 24V / 1300mA NI-CD Battery		